



Consolated Bearing CO.,LTD

1.063 Inch | 27 Millimeter x 1.5 Inch | 38.1
Millimeter x 1.688 Inch | 42.875 Millimeter NTN
UCP206-101D1 Pillow Block Bearings



UCP206-101D1 Bearing 2D drawings and 3D CAD models

Bearing No. UCP206-101D1

Category	Pillow Block Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight	1.41
EAN	4547359503098
Product Group	M06110
Number of Mounting Holes	2
Mounting Method	Set Screw
Housing Style	2 Bolt Pillow Block
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	1/2 Inch
Relubricatable	Yes
Insert Part Number	UC206-101D1
Seals	Single Lip Land Riding
Housing Configuration	1 Piece Solid
Inch - Metric	Inch
Other Features	Single Row Light Duty Wide Inner Race Has Flinger
Long Description	2 Bolt Pillow Block; 1-1/16" Bore; 1-11/16" Base to Center Height; Set Screw Mount; Ball Bearing;



Consolated Bearing CO.,LTD

	Relubricatable; Cast Iron; Single Lip Land Riding; Non-expansion
Category	Pillow Block
UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Pillow Block
Manufacturer URL	http://www.ntnamerica.com
Manufacturer Item Number	UCP206-101D1
Weight / LBS	3.1
D	1.5 Inch 38.1 Millimeter
Bolt Spacing Maximum	0 Inch 0Millimeter
Actual Bolt Center to Center	4.8 Inch 121Millimeter
d	1.063 Inch 27 Millimeter
Bolt Spacing Minimum	0 Inch 0Millimeter
Nominal Bolt Center to Center	4.8 Inch 121 Millimeter
B	1.688 Inch 42.875 Millimeter
mounting:	Two-Bolt Base
finish/coating:	Uncoated
bore diameter:	1.0625 in
overall width:	1-1/2 in
bore type:	Round
radial dynamic load capacity:	4400 lb
base to bore centerline:	1.6875 in
radial static load capacity:	2540 lb
duty type:	Light Duty
base width:	1-7/8 in
housing material:	Cast Iron



Consolated Bearing CO.,LTD

bolt center-to-center length:	4-3/4 in
locking device:	Set Screw
lubrication type:	Lubrication Fitting
seal type:	Contact with Flinger
series:	UCP2
expansion type:	Non-Expansion Bearing (Fixed)
replacement bearing:	UC206-101D1
overall length:	6.5000 in
standards met:	ANSI, ISO, AFBMA
overall height:	3.2813 in